

Data Sheet for Article: MX363342F2

Combination MCCB Type EN, 4P, 70kA, 630A and RCD up to 2A

Rated current 630A, Short circuit switching capacity (400V) 70kA, Size type 3, Tripping Unit
Electronic release - Type EN, Poles 4, Rated residual current: 100mA-300mA-1A-2A

The logo consists of the letters 'MX' in a large, bold, sans-serif font, with the word 'SERIE' in a smaller, bold, sans-serif font directly below it. The entire logo is centered within a white rectangular area that has a thin red border.

Technical Data

Net width (mm)	185,00
Net height (mm)	355,00
Net weight (kg)	0,84
EAN	9004840905922
Power loss (W)	190,40
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	70
Device category	circuit breaker
Standard	EN 60947-2
Rated current (A)	630
Rated voltage	< 690VAC
Short circuit switching capacity (400V) (kA)	70
Size type	3
Tripping Unit	Electronic release - Type EN
Poles	4
Pollution degree	3

Technical Data - continued

IP Rating	IP40
Mechanical durability	15000 operation cycles
Rated insulation voltage [Ui] (V)	1000
Rated impulse withstand voltage [Uimp] (V)	12000
Rated ultimate short-circuit breaking capacity Icu (kA)	70
Rated service breaking capacity Ics (kA)	70
AC 380/400/415V	70kA (Icu) / 70kA (Ics)
AC 440V	70kA (Icu) / 70kA (Ics)
AC 500V	40kA (Icu) / 40kA (Ics)
AC 660/690V	12kA (Icu) / 12kA (Ics)
Electrical endurance (Operation cycle)	
AC 415V, In	3000
AC 690V, In	1500

Article Table

DESCRIPTION	Order No.
Combination MCCB Type EN, 4P, 70kA, 630A and RCD up to 2A Rated current 630A, Short circuit switching capacity (400V) 70kA, Size type 3, Tripping Unit Electronic release - Type EN, Poles 4, MX363342F2 Rated residual current: 100mA-300mA-1A-2A	
Optional Accessories	
Communication module Modbus-RTU 24VDC 1.5m	MX290000
Communication module Modbus-RTU 230VAC 1.5m	MX290001
Toggle Lever Locking Device for MX3	MX390199
Box Terminal for MX3 120-240MM ² , 1 piece Size type 3, Al/Cu	MX390015
Connection extension 4 pole for MX3, 8 pieces Poles 4, 8 pieces included per item, for 4-pole MX3 (for top and bottom)	MX390020
Terminal Cover short 4 pole for MX3 Poles 4, for top and bottom	MX390781
Terminal Cover long 4 pole for MX3 Poles 4, for top and bottom	MX390784
Tunnel Terminal 2x120-240mm ² for MX3, 1 piece, max. 500A Size type 3, Al/Cu, control connection: M3, not more than 80% of the rated current for Aluminum, not maintenance-free for Aluminum, attend to connection conditions!!	MX396730
Tunnel Terminal 4x95mm ² for MX3, 1 piece, max. 500A Size type 3, Al/Cu, control connection: M3, not more than 80% of the rated current for Aluminum, not maintenance-free for Aluminum, attend to connection conditions!!	MX396731
Rear Connection, 4P for MX3, for both connection sides Size type 3	MX396735
Socket for MX3 4 pole Size type 3, Poles 4	MX396872
Safety release for socket MX3 for thermal release Size type 3	MX396873
Safety release for socket MX3 for electronic release Size type 3	MX396874
Phase separator plates MX3 Size type 3	MX396870
Rotary Handle complete, lockable for MX3 for thermal release	MX390125
Rotary Handle complete, lockable for MX3 for electr. release	MX390126
Door Coupling Rotary Handle, for MX3 for thermal release Size type 3, Axle length 50cm	MX390172
Door Coupling Rotary Handle, for MX3 for electronic release Size type 3, Axle length 50cm	MX390173

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Mechanical Interlock for MX3 4 pole Size type 3, Poles 4	MX391582
Under Voltage Release 110VAC for MX2, MX3 Size type 2,3	MX299462
Under Voltage Release 220-240VAC for MX2, MX3 Size type 2,3	MX299471
Under Voltage Release 380-415VAC for MX2, MX3 Size type 2,3	MX299473
Under Voltage Release 24VDC for MX2, MX3 Size type 2,3	MX299481
Under Voltage Release 220VDC for MX2, MX3 Size type 2,3	MX299489
Shunt trip 110VAC for MX2, MX3	MX299567
Shunt trip 220-240VAC for MX2, MX3	MX290154
Shunt trip 380-415VAC for MX2, MX3	MX291607
Shunt trip 24VDC for MX2, MX3	MX299736
Shunt trip 220VDC for MX2, MX3	MX299742
Remote Operator 24VDC for MX3 Size type 3	MX399837
Remote Operator 110VAC/110-120VDC for MX3 Size type 3	MX399838
Remote Operator 220-240VAC/220VDC for MX3 Size type 3	MX399832
Remote Operator 380-415VAC for MX3 Size type 3	MX399833
RCD für MX3 4 pole Typ A 50-200mA-0.5-1A	MX394610
RCD für MX3 4 pole Typ A 100-300mA-1-2A	MX394612
Auxiliary contact 1 CO	MX199411
Alarm contact 1 CO	MX199511