

Data Sheet for Article: NLAMWE03SC

Self-contained luminaire AM LED 3h 230V AC wall surface

stainless steel look, 1h/3h/8h adjustable



Technical Data


Net length (mm)	241,00
Net width (mm)	50,00
Net height (mm)	151,00
Net weight (kg)	1,15
Luminaire type	emergency sign luminaire
Self contained - central battery	Self contained luminaire
Function	self controlled
Version	edge luminaire
Design	AM
Colour	stainless steel appearance
Pictogram	Slide-in pictogram set (arrow left, right, bottom, top and white foil for single side use) included in accordance with ISO 7010
Viewing distance (m)	22
Backup time (h)	3
Illuminant	LED (2W)
Voltage range (V)	230V AC 50Hz ±20%
Battery (V/Ah)	4,8/2,0 NiMh
IP Rating	IP40
Mounting	surface mounting wall
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	40
AA Class E 8101	AA4

Technical Data - continued

Manufacturer

Schrack

Dimensions (mm)



Article Table

DESCRIPTION	Order No.
Self-contained luminaire AM LED 3h 230V AC wall surface stainless steel look, 1h/3h/8h adjustable	NLAMWE03SC
Optional Accessories	
Plug-pictogram left top for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLO
Plug-pictogram left bottom for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLU
Plug-pictogram right top for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRO
Plug-pictogram right bottom for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRU
Pictograph set "fire protection" VD: 22 m.. (2x4 pcs.) pictographs according to ISO 7010 included: fire extinguisher, fire hose reel, fire alarm call point, collection of firefighting equipment, suitable for design KS, AM, KB	NLKS4FIRE
Concrete plaster box for emergency luminaire Design AM/AX	NLAMAXBE
Accu NiMH 4,8V 2,0Ah for self contained luminaires LED LPU or LEM module	NLAKKU4820