

Data Sheet for Article: NLDEQ023SC

Emerg.lum.DEQ 3x1W ERT-LED 3h 230V AC Self C.recessed m


1h/3h/8h adjustable



Technical Data

Net length (mm)	270,00
Net width (mm)	90,00
Net height (mm)	110,00
Luminaire type	safety luminaire
Self contained - central battery	Self contained luminaire
Function	self controlled
Version	metal luminaire
Design	DEQ
Colour	White
Backup time (h)	3
Illuminant	ERT-LED (3W)
Lumen	1h: 300;3h: 180;8h: 84
Voltage range (V)	230V AC 50Hz $\pm 20\%$
Battery (V/Ah)	4,8/2,0 NiMh
IP Rating	IP20
Mounting	recessed mounting ceiling
AA Class E 8101	AA4

Dimensions (mm)



Distance table - min. illumination at the middle line: 1lx - maintenance factor 0,80 - 1h autonomy time

Montagehöhe [m]					
2	3,93	10,98	11,17	10,99	3,76
2,5	3,57	11,21	11,21	11,10	3,44
3	2,61	11,10	11,01	10,93	2,52
3,5	1,56	10,11	10,06	9,89	1,00
4	0,00	7,83	8,35	8,24	0

Distance table - min. illumination at the middle line: 1lx - maintenance factor 0,80 - 3h autonomy time

Montagehöhe [m]					
2,00	2,65	8,70	8,65	8,59	2,56
2,50	1,69	8,42	8,33	8,23	1,39
3,00	0,00	6,63	6,73	6,64	0,00
3,50	0,00	4,78	5,15	4,65	0,00
4,00	0,00	1,64	2,23	2,18	0,00

Article Table

DESCRIPTION	Order No.
Emerg.lum.DEQ 3x1W ERT-LED 3h 230V AC Self C.recessed m 1h/3h/8h adjustable	NLDEQ023SC
Optional Accessories	
Accu NiMH 4,8V 2,0Ah for self contained luminaires LED LPU or LEM module	NLAKKU4820
Ball Protection gascet for IL, KI, VI, RI, KT, DAQ, DAR	NLBALL3