

EX-protect.emerg.luminaire design EX zone2/22 LED 230V AC/DC

without pictogram, for CPS and LPS, wall or ceiling surface mounting, IP66, type: BASET-N-LED-1R-1300-4K, 1160lm



Technical Data

Net length (mm)	338,00
Net height (mm)	176,00
Netto depth (mm)	110,00
Net weight (kg)	0,98
Luminaire type	safety luminaire
Self contained - central battery	Central power supply luminaire
Function	standard
Version	explosion proof luminaire
Design	EX
Colour	Grey
Illuminant	HP-LED (8W)
Lumen	1160
Voltage range (V)	230V AC 50Hz $\pm 20\%$; 230V DC $\pm 20\%$
Power (W)	9
IP Rating	IP66
Mounting	surface mounting ceiling surface mounting wall
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	50
AA Class E 8101	AA3 AA4

Datei Tabelle: EX-protect.emerg.luminaire design EX zone2/22 LED 230V AC/DC

					
2,00	4,97	12,39	11,75	11,08	4,52
2,50	6,20	15,47	14,67	13,83	5,64
3,00	6,59	16,58	15,77	14,94	6,06
3,50	6,93	17,51	16,72	15,93	6,41
4,00	7,22	18,33	17,56	16,79	6,70
5,00	7,65	19,71	18,97	18,22	7,15
6,00	7,91	20,81	20,07	19,34	7,46
7,00	8,03	21,61	20,90	20,21	7,62
8,00	8,02	22,19	21,52	20,86	7,66
9,00	7,89	22,57	21,94	21,33	7,58
10,00	7,65	22,77	22,17	21,60	7,36
12,00	6,71	22,59	22,09	21,62	6,51
14,00	4,89	21,74	21,33	20,94	4,84

Article Table

DESCRIPTION	Order No.
EX-protect.emerg.luminaire design EX zone2/22 LED 230V AC/DC without pictogram, for CPS and LPS, wall or ceiling surface mounting, IP66, type: BASET-N-LED-1R-1300-4K, 1160lm	NLEXU019
Optional Accessories	
Light manager for CPS including mixed mode 4-200VA	NLMU06
Box IP65 with mounting plate + MU06 f. luminaires 4-200VA 176x125x82 mm (LxHxD)	NLMU06BOX
Adhesive pictogram, arrow left, viewing distance: 20m Viewing distance: 20m	NLLTPLI
Adhesive pictogram, arrow right, viewing distance: 20m Viewing distance: 20m	NLLTPRE
Adhesive pictogram, arrow up, viewing distance: 20m Viewing distance: 20m	NLLTPOB
Adhesive pictogram, arrow down, viewing distance: 20m Viewing distance: 20m	NLLTPUN