

Data Sheet for Article: NLEXU019EL

EX-protect.emerg.lumin. design EX zone2/22 LED 230VAC/DC EL

with supervision - centrally switchable, without pictogram, for CPS and LPS, wall or ceiling surface mounting, IP66, type: BASET-N-LED-1R-1300-4K



Technical Data

Net length (mm)	338,00
Net height (mm)	176,00
Netto depth (mm)	110,00
Net weight (kg)	0,98
Luminaire type	safety luminaire
Self contained - central battery	Central power supply luminaire
Function	with monitoring - centrally switchable
Version	explosion proof luminaire
Design	EX
Colour	Grey
Illuminant	HP-LED (8W)
Voltage range (V)	230V AC 50Hz $\pm 20\%$; 230V DC $\pm 20\%$
Power (W)	9

Technical Data - continued

IP Rating	IP66
Mounting	surface mounting ceiling surface mounting wall
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	35
AA Class E 8101	AA3 AA4

Article Table

DESCRIPTION	Order No.
EX-protect.emerg.lumin. design EX zone2/22 LED 230VAC/DC EL with supervision - centrally switchable, without pictogram, for CPS and LPS, wall or ceiling surface mounting, IP66, type: BASET-N- NLEXU019EL LED-1R-1300-4K	
Optional Accessories	
Adhesive pictogram, arrow left, viewing distance: 20m Viewing distance: 20m	NLLTPLI
Adhesive pictogram, arrow right, viewing distance: 20m Viewing distance: 20m	NLLTPRE
Adhesive pictogram, arrow up, viewing distance: 20m Viewing distance: 20m	NLLTPOB
Adhesive pictogram, arrow down, viewing distance: 20m Viewing distance: 20m	NLLTPUN