




Emerg.lum. IL WirelessControl 1x3W ERT-LED 3h 230V AC

Black, White, surface ceiling mounting, LiFePO4 battery, emergency luminaire with exchangeable lenses, including lenses for illuminating escape routes or for illuminating round surfaces, central switching, 250lm




Technical Data

Net height (mm)	36,00
Net diameter (mm)	99,00
Net weight (kg)	0,25
Luminaire type	safety luminaire
Self contained - central battery	Self contained luminaire
Function	WirelessControl Professional
Version	Plastic luminaire
Design	IL
Halogen-free	Housing made of halogen-free plastic
Colour	RAL 9005 (black)
Backup time (h)	3
Illuminant	ERT-LED (3W)


Technical Data - continued

Lumen	250
Voltage range (V)	230V AC 50Hz $\pm 20\%$
Power maintained mode (W)	2,30
Power non-maintained mode (W)	0,40
Power max. (W)	3,40
Battery (V/Ah)	3,2/3,3 LiFePO4
IP Rating	IP40
Impact Resistance	$\geq IK03$
Mounting	surface mounting ceiling recessed mounting ceiling optional
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	30
AA Class E 8101	AA4
Manufacturer	Schrack


Dimensions NLILD... (mm)




Dimensions accessoires NLILIP65 (mm)



Dimensions accessoires Zinc die-cast housing NLEA.. (mm)



Wall illumination 5 lux for safety devices with optional beam lens (NLLSYSB4)
- Maintenance factor 0.8 - 1h/3h



Spacing table with corridor lens (included in scope delivery) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - autonomy time 3h

					
2,00	2,45	6,67	10,92	15,17	6,67
2,50	2,50	6,89	12,22	17,50	7,71
3,00	2,45	7,10	13,48	19,76	8,56
3,50	2,35	7,18	14,50	21,83	9,28
4,00	2,40	7,15	15,32	23,59	9,89
5,00	2,06	7,10	12,19	22,97	2,87

Spacing table with round lens (included in scope of delivery) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - autonomy time 3h

					
2,00	3,96	8,47	8,47	8,47	3,96
2,50	4,74	10,16	10,16	10,16	4,74
3,00	5,34	11,81	11,81	11,81	5,34
3,50	5,60	13,34	13,34	13,34	5,60
4,00	1,88	12,07	12,07	12,07	1,88

Spacing table with spot lens (must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - autonomy time 3h

					
2,00	1,77	3,97	3,97	3,97	1,77
2,50	2,15	4,86	4,86	4,86	2,15
3,00	2,42	5,55	5,55	5,55	2,42
3,50	2,71	6,13	6,13	6,13	2,71
4,00	2,95	6,63	6,63	6,63	2,95
5,00	3,36	7,78	7,78	7,78	3,36
6,00	3,73	8,70	8,70	8,70	3,73
7,00	3,99	9,52	9,52	9,52	3,99
8,00	4,13	10,29	10,29	10,29	4,13
9,00	4,17	10,91	10,91	10,91	4,17
10,00	4,12	11,38	11,38	11,38	4,12
12,00	3,71	11,83	11,83	11,83	3,71
14,00	2,80	11,73	11,73	11,73	2,80

Spacing table with high corridor lens (must be ordered separately) - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80 - autonomy time 3h

					
2,00	1,68	4,18	7,30	10,25	4,41
2,50	1,85	4,75	8,28	11,83	4,99
3,00	1,55	5,09	9,09	13,22	5,47
3,50	1,50	5,14	9,72	14,38	5,86
4,00	1,49	4,97	10,14	15,35	6,19
5,00	1,66	4,30	10,51	16,99	6,63
6,00	1,78	4,30	10,80	18,26	6,80
7,00	1,82	4,69	11,06	19,13	6,80
8,00	1,88	4,96	11,07	19,55	6,66
9,00	1,86	5,08	10,89	19,70	6,38
10,00	1,76	5,19	10,75	19,64	5,87
12,00	1,36	5,32	9,72	18,94	4,27

Article Table

DESCRIPTION	Order No.
Emerg.lum. IL WirelessControl 1x3W ERT-LED 3h 230V AC	
Black, White, surface ceiling mounting, LiFePO4 battery, emergency luminaire with exchangeable lenses, including lenses for illuminating escape routes or for illuminating round surfaces, central switching, 250lm	NLILDLS23W
Optional Accessories	
Recessed frame black for emergency luminaires NLILD..	NLILDES
Required ceiling cut out: diameter 114 mm	
Spacer plate black for NLILD.. for cable entry at the side	NLILDAPA2S

Article Table

DESCRIPTION	Order No.
Optional Accessories	
4 LED changeable lens: Spot area illumination for high rooms Suitable for emergency luminaires with changeable lens system	NLLSYSS4
Square plug over housing B1 for emergency luminaires NLILD..	NLILB1
Square plug over housing B2 for emergency luminaires NLILD..	NLILB2
Plug over housing white round zinc die cast Universal ceiling mounting cover for the luminaires NLILDR.. NLILDF.. or NLILDS	NLEAR
Plug over housing anthracite round zinc die cast Universal ceiling mounting cover for the luminaires NLILDR.. NLILDF.. or NLILDS	NLEARAZ
Plug over housing white square zinc die cast Universal ceiling mounting cover for the luminaires NLILDR.. NLILDF.. or NLILDS	NLEAQ
Plug over housing anthracite square zinc die cast Universal ceiling mounting cover for the luminaires NLILDR.. NLILDF.. or NLILDS	NLEAQAZ
Ball Protection basket for IL, KT, DAQ, DAR, S2 l x h x d: 200 x 200 x 90mm	NLBALL3
Surface mounted housing white IP65 for emerg. Lumin. NLILD Polycarbonate, with side cable entries	NLILIP65K
Accu LiFePO4 3,2V 3,3Ah for LED luminaire For design KM, KSC, KMB, ASM, ZAW, NLILL.23., LiFePO4 - Lithium-iron phosphates battery, UN3480 - UN 3480 : Lithium-Ion batteries, compatible to accu 3,2V 3,3Ah	NLAKKU3230
IP65 housing for IL ceiling mounted luminaires, anthracite Suitable for surface-mounted emergency ceiling lights NLILD..., including spacer plate, vandal-proof with shock resistance test according to IK10, ball impact resistant according to DIN 18032	NLILIK10A