

Data Sheet for Article: NLK2U009--

Emergency luminaire K2 LED 230V AC/DC universal mounting

Viewing distance: 27m



Technical Data


Net length (mm)	280,00
Net width (mm)	45,00
Net height (mm)	194,00
Net weight (kg)	0,65
Luminaire type	emergency sign luminaire
Self contained - central battery	Central power supply luminaire
Function	standard
Version	Plastic luminaire
Design	K2
Halogen-free	Housing made of halogen-free plastic
Colour	White
Pictogram	Slide-in pictogram set (arrow left, right, bottom, top and white foil for single side use) included in accordance with ISO 7010
Viewing distance (m)	27

Technical Data - continued


Illuminant	LED (3W)
Voltage range (V)	230V AC 50Hz $\pm 20\%$; 230V DC $\pm 20\%$
IP Rating	IP44
Impact Resistance	IK03
Mounting	surface mounting ceiling surface mounting wall recessed mounting ceiling optional universal
Min. ambient temperature (°C)	-30
Max. ambient temperature (°C)	40
AA Class E 8101	AA3 AA4
Manufacturer	Schrack

Dimensions (mm)


NLK2U




NLK2U + NLK2E



NLK2U + NLK1AW



Dimensions (mm)



Article Table

DESCRIPTION	Order No.
Emergency luminaire K2 LED 230V AC/DC universal mounting Viewing distance: 27m	NLK2U009
Optional Accessories	
Recessed frame white Required ceiling cut out: 320 x 75 mm	NLK2E2
Wall bracket white f. emergency luminaires Design K2, K3	NLK1AW
Pendant 500 mm white for emergency luminaires	NLK1P105