

Data Sheet for Article: NLKMB509CC

Emergency luminaire KMB 4x0, 5W LED CC24 24V universal mount.

White, with supervision - centrally switchable, 220lm



Technical Data


Net length (mm)	250,00
Net width (mm)	34,00
Net height (mm)	50,00
Net weight (kg)	0,30
Luminaire type	safety luminaire
Self contained - central battery	Central power supply luminaire
Function	24V Core24 with supervision- centrally switchable
Version	Plastic luminaire
Design	KMB
Halogen-free	Housing made of halogen-free plastic
Colour	White
Illuminant	LED (2W)
Lumen	220
Voltage range (V)	24V AC

Technical Data - continued




Power maintained mode (W)	2,10
Power non-maintained mode (W)	0,40
Power max. (W)	2,10
IP Rating	IP54
Impact Resistance	≥ IK03
Mounting	surface mounting ceiling surface mounting wall recessed mounting ceiling optional universal
Min. ambient temperature (°C)	-30
Max. ambient temperature (°C)	40
AA Class E 8101	AA3 AA4 AA5
Manufacturer	Schrack

Dimensions (mm)

NLKMB...



NLKME



Article Table

DESCRIPTION	Order No.
Emergency luminaire KMB 4x0,5W LED CC24 24V universal mount. White, with supervision - centrally switchable, 220lm	NLKMB509CC
Optional Accessories	
Recessed frame white for CPS emergency luminaires KM,KMB,KS Required ceiling cut out: 277 x 56 mm	NLKME
Concrete plaster box f. emergency luminaire Design KMB,KS,KM	NLKMBE
Wall bracket white for luminaires Design KM/KS	NLAWKSU
Design pair of pendants 500 mm white, wired Suitable for design KS, KM, KMB in self contained version with LiFePO4 battery	NL2DWKMKS
Design cord suspension 2000mm, 1 pair	NLDSA000
Cord suspension 2000mm, 1 pair	NLCORD2
Cord suspension 4000mm, 1 pair	NLCORD4