

Emergency lum.KS 4x0,5W LED CC24 24V, universal mount., black

with supervision - centrally switchable, with 4x0,5W High Power LED, with transparent cover for additional light of the rescue path, viewing distance: 22m, 220lm



Technical Data



Net length (mm)	250,00
Net width (mm)	34,00
Net height (mm)	174,00
Net weight (kg)	0,62
Luminaire type	safety luminaire emergency sign luminaire Combined rescue path and rescue sign luminaire
Self contained - central battery	Central power supply luminaire
Function	24V Core24 with supervision- centrally switchable
Version	Plastic luminaire edge luminaire
Design	KS
Halogen-free	Housing made of halogen-free plastic

Technical Data - continued




Colour	RAL 9005 (black)
Viewing distance (m)	22
Illuminant	LED (2W)
Lumen	220
Voltage range (V)	24V AC
Power maintained mode (W)	2,10
Power non-maintained mode (W)	0,40
Power max. (W)	2,10
IP Rating	IP54
Impact Resistance	≥ IK03
Mounting	surface mounting ceiling surface mounting wall recessed mounting ceiling optional universal
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	40
AA Class E 8101	AA4
Manufacturer	Schrack

Dimensions (mm)



NLKS...



NLKME



Drilling distances (mm)



Spacing table - Min. illuminance on the center line +/- 0.5 m: 1 lx - Maintenance factor 0.80

					
2,00	3,07	7,54	7,42	6,91	2,76
2,50	2,95	8,36	8,09	7,52	3,13
3,00	1,28	7,33	7,06	8,16	3,24
3,50	1,24	6,66	6,47	8,85	3
4,00	1,27	3,67	6,42	9,15	2,91
5,00	1,15	3,52	5,79	8,41	2,15

Article Table

DESCRIPTION	Order No.
Emergency lum.KS 4x0,5W LED CC24 24V,universal mount., black with supervision - centrally switchable, with 4x0,5W High Power LED, with transparent cover for additional light of the rescue path, viewing distance: 22m, 220lm	NLKSCS509C
Optional Accessories	
Recessed frame black for CPS luminaires Design KM,KMB,KS Required ceiling cut out: 277 x 56 mm	NLKMES
Plug-pictogram left top for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLO
Plug-pictogram left bottom for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLU
Plug-pictogram right top for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRO
Plug-pictogram right bottom for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRU
Pictograph set "fire protection" VD: 22 m.. (2x4 pcs.) pictographs according to ISO 7010 included: fire extinguisher, fire hose reel, fire alarm call point, collection of firefighting equipment, suitable for design KS, AM, KB	NLKS4FIRE
Pictograph set "first aid" vd: 22m (2x4 pcs.) pictographs according to ISO 7010 included: first aid, Hazard duty point, Automated heart defibrillator, emergency window with escape ladder, suitable for design KS, AM, KB	NLKS4HELP
Wall bracket white for luminaires Design KM/KS	NLAWKSU
Design pair of pendants 500 mm white, wired Suitable for design KS, KM, KMB in self contained version with LiFePO4 battery	NL2DWKMKS
Ball Protection for KD, KM, KS,LM, VM, RI, RM l x h x d: 320 x 220 x 120mm	NLBALL1
Design cord suspension 2000mm, 1 pair	NLDSA000
Cord suspension 2000mm, 1 pair	NLCORD2
Cord suspension 4000mm, 1 pair	NLCORD4