

Data Sheet for Article: NLKSW003SC

Self-contained luminaire KS self-contr. LED 3h 230V AC univ.

Erkennungsweite: 22m




Technical Data

Net length (mm)	250,00
Net width (mm)	34,00
Net height (mm)	174,00
Net weight (kg)	0,60
Luminaire type	emergency sign luminaire
Self contained - central battery	Self contained luminaire
Function	self controlled
Version	edge luminaire
Design	KS
Halogen-free	Housing made of halogen-free plastic
Colour	White
Pictogram	Slide-in pictogram set (arrow left, right, bottom, top and white foil for single side use) included in accordance with ISO 7010
Viewing distance (m)	24
Backup time (h)	3
Illuminant	LED (2W)
Voltage range (V)	230V AC 50Hz $\pm 20\%$
Battery (V/Ah)	4,8/0,5 NiMh
IP Rating	IP54



Technical Data - continued

Mounting	surface mounting ceiling surface mounting wall recessed mounting ceiling universal
AA Class E 8101	AA4
Manufacturer	Schrack

Dimensions (mm)



Drilling distances (mm)



Article Table

DESCRIPTION	Order No.
Self-contained luminaire KS self-contr. LED 3h 230V AC univ. Erkennungsweite: 22m	NLKSU003SC
Optional Accessories	
Accu NiMH 4,8V 0,5Ah for self cont. luminaires LED KM and KS Suitable for NLKMU033SC and NLKSU003SC	NLAKKU4805
Plug-pictogram left top for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLO
Plug-pictogram left bottom for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTLU
Plug-pictogram right top for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRO
Plug-pictogram right bottom for Design AM, KBM, KS, VM viewing distance: 22m	NLAMPIKTRU
Pictograph set "fire protection" VD: 22 m.. (2x4 pcs.) pictographs according to ISO 7010 included: fire extinguisher, fire hose reel, fire alarm call point, collection of firefighting equipment, suitable for design KS, AM, KB	NLKS4FIRE
Pictograph set "first aid" vd: 22m (2x4 pcs.) pictographs according to ISO 7010 included: first aid, Hazard duty point, Automated heart defibrillator, emergency window with escape ladder, suitable for design KS, AM, KB	NLKS4HELP
Wall bracket white for luminaires Design KM/KS	NLAWKSU
Design pair of pendants 500 mm white, wired Suitable for design KS, KM, KMB in self contained version with LiFePO4 battery	NL2DWKMKS
Ball Protection for KD, KM, KS, LM, VM, RI, RM	NLBALL1
Design cord suspension 2000mm, 1 pair	NLDSA000
Cord suspension 2000mm, 1 pair	NLCORD2
Cord suspension 4000mm, 1 pair	NLCORD4