

Data Sheet for Article: NLMN100X17

Low Power Supply MiniControl XL, 32/20 without DCM

including batteries, without el. circuit module DCM, max. load: 1500W 1h / 500W 3h / 300W 8h, optionally extendable to max. 32 electrical circuits 640 luminaires, h1500 x w610 x d290mm



Technical Data

Net width (mm)	610,00
Net height (mm)	1.500,00
Netto depth (mm)	290,00
Net weight (kg)	149,00

Article Table

DESCRIPTION	Order No.
Low Power Supply MiniControl XL, 32/20 without DCM including batteries, without el. circuit module DCM, max. load: 1500W 1h / 500W 3h / 300W 8h, optionally extendable to max. NLMN100X17 32 electrical circuits 640 luminaires, h1500 x w610 x d290mm	
Necessary Accessories	
Mains circuit module DCM for 2 el. circuits 19" 2x1A For individually centrally switchable emergency luminaires NL..EL, NL...E, max. load 2 x 300VA – fuse 4x F5A, 6,3x32mm. Suitable NLDCM12E for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	
Electric Circuit Unit f. 2 Circuits DCM 19" 2x3A main/non-m Max. load 2 x 650VA – fuse 4x F5A, 6,3x32mm. Suitable for LPS and CPS Micro-, Mini-, Midi-, Maxi- or MultiControl	NLDCM32
Optional Accessories	
E30 fire protection panel for MiniControlXL MNXL with fan Outside dimensions: 1828 x 908 x 434 mm (HxWxD), inside dimensions: 1650 x 730 x 310 mm, colour: RAL7035, 263kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNXLE30A
3-phase line monitor with bus communication for Multicontrol	NLMCLM
Three phase power supply monitoring	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S