

Data Sheet for Article: NLMN102A05

Low Power Supply MiniControl 2 circ. total max. 40 lamps

Max. load: 500W 1h / 200W 3h, optionally extendable to max. 12 electrical circuits 240
luminaires



Technical Data

Net length (mm)	230,00
Net width (mm)	500,00
Net height (mm)	1.100,00
Net weight (kg)	140,01

Article Table

DESCRIPTION	Order No.
Low Power Supply MiniControl 2 circ. total max. 40 lamps Max. load: 500W 1h / 200W 3h, optionally extenable to max. 12 electrical circuits 240 luminaires	NLMN102A05
Optional Accessories	
E30 fire protection panel for LPS MiniControl MN with fan Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Plexiglas cover with lock for LPS Minicontrol	NLPLXMIN
3-phase line monitor with bus communication for Multicontrol	NLMCLM
Three phase power supply monitoring	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S