

Data Sheet for Article: NLMN108A--

Low Power Supply MiniControl 8 circ. total max. 160 lumin.

8 electrical circuits, max. 160 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1 h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm



Technical Data

Net length (mm)	230,00
Net width (mm)	500,00
Net height (mm)	1.100,00
Net weight (kg)	140,01

Article Table

DESCRIPTION	Order No.
Low Power Supply MiniControl 8 circ. total max. 160 lumin.	
8 electrical circuits, max. 160 luminaires (20 luminaires per circuit), max. power rating: 1500 W 1h / 500 W 3 h / 300 W 8 h, optionally expandable to max. 12 circuits max. 240 luminaires, h x w x d: 1100 x 500 x 230 mm	NLMN108A
Optional Accessories	
E30 fire protection panel for LPS MiniControl MN with fan	
Outside dimensions: 1388 x 861 x 345mm (HxWxD), colour RAL7035, 115kg, functional preservation 30 minutes - according to E30, fire resistance 30 minutes - according to F30/I30	NLMNE30
Plexiglas cover with lock for LPS Minicontrol	NLPLXMIN
3-phase line monitor with bus communication for Multicontrol	NLMCLM
Three phase power supply monitoring	NLPC2300
Light switch query module 8 inp.incl.mains monitor, separate	NLSAM24
Indicator panel with LCD clear text display and bus comm.	NLMCT15
Indicator panel with LCD display, key switch and bus comm. With key switch	NLMCT15S