

Data Sheet for Article: NLPXW403SC

Self-contained lumin. PX selfcontrol LED/ 1h 3h 230V AC wall

wall mounting, 1h/3h/8h adjustable, viewing distance: 30m, LiFePO4 battery



Technical Data

Net length (mm)	340,00
Net width (mm)	60,00
Net height (mm)	170,00
Net weight (kg)	0,80
Luminaire type	emergency sign luminaire
Self contained - central battery	Self contained luminaire
Function	self controlled
Version	Plastic luminaire
Design	PX
Halogen-free	Housing made of halogen-free plastic
Colour	RAL 9003 (white)
Pictogram	Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010
Viewing distance (m)	30

Technical Data - continued

Illuminant	LED (3W)
Voltage range (V)	230V AC 50Hz ±20%
Power maintained mode (W)	1,70
Power non-maintained mode (W)	0,90
Power max. (W)	3,20
Battery (V/Ah)	2x 3,2V/1,6Ah LiFePO4
IP Rating	IP65
Impact Resistance	IK05
Mounting	surface mounting wall
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	40
AA Class E 8101	AA4
Manufacturer	Schrack

Article Table

DESCRIPTION	Order No.
Self-contained lumin. PX selfcontrol LED/1h 3h 230V AC wall wall mounting, 1h/3h/8h adjustable, viewing distance: 30m, LiFePO4 battery	NLPXW403SC
Optional Accessories	
Rain cover for emergency luminaires Design KC plexiglass	NLKCRD
Ball Protection for KC, KB+KBG, KX, PF, LX, C2 l x h x d: 450 x 280 x 125mm	NLBALL2
Pictogram set for NLPX.. 2x wheelchair, 2x arrows diagonal 2 part pictograms, vd: 30m	NLPXPIKTO2
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV
Set 2 accus LiFePO4 3,2V 1,6Ah f. luminaires. w. LEO or LPK LiFePO4 - Lithium-iron phoshpate battery , UN3480 - UN 3480 : Lithium-Ion batteries	NLAKKU3216