

Data Sheet for Article: NLPXW403WL

Emerg. luminaire PX WirelessControl LED 3h 230V AC

wall surface mounting, viewing distance: 30m, radio switchable, with LiFePO4 battery, 140lm



Technical Data

Net length (mm)	340,00
Net width (mm)	60,00
Net height (mm)	170,00
Net weight (kg)	0,90
Luminaire type	emergency sign luminaire
Self contained - central battery	Self contained luminaire
Function	WirelessControl Professional
Version	Plastic luminaire
Design	PX
Halogen-free	Housing made of halogen-free plastic
Colour	RAL 9003 (white)
Pictogram	Slide-in pictogram set (2x man in the door and one arrow that can be rotated by 90°) included in accordance with ISO 7010
Viewing distance (m)	30

Technical Data - continued

Backup time (h)	3
Illuminant	LED (3W)
Lumen	140
Voltage range (V)	230V AC 50Hz $\pm 20\%$
Power maintained mode (W)	2
Power non-maintained mode (W)	0,80
Power max. (W)	4
Battery (V/Ah)	2x 3,2V/1,6Ah LiFePO4
IP Rating	IP65
Impact Resistance	IK05
Mounting	surface mounting wall
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	40
AA Class E 8101	AA4
Manufacturer	Schrack

Article Table

DESCRIPTION	Order No.
Emerg. luminaire PX WirelessControl LED 3h 230V AC wall surface mounting, viewing distance: 30m, radio switchable, with LiFePO4 battery, 140lm	NLPXW403WL
Optional Accessories	
Rain cover for emergency luminaires Design KC plexiglass	NLKCRD
Ball Protection for KC, KB+KBG, KX, PF, LX, C2 l x h x d: 450 x 280 x 125mm	NLBALL2
Pictogram set for NLPX.. 2x wheelchair, 2x arrows diagonal 2 part pictograms, vd: 30m	NLPXPIKTO2
	NLTESTSC2
Protective cover for test buttons NLTEST2---	NLTEST2COV
Set 2 accus LiFePO4 3,2V 1,6Ah f. luminaires. w. LEO or LPK LiFePO4 - Lithium-iron phoshpate battery , UN3480 - UN 3480 : Lithium-Ion batteries	NLAKKU3216