

Data Sheet for Article: SR1428215C

SCRAX 42HE-19"Enclosure, Vent. Doors, B=800xT=1.200xH=2.005mm

By activating the "Request shopping cart" button, the customer advisor assigned to you will be informed and will contact you immediately.



SCHRACK-Info

- SCRAX server rack with 2 depth-adjustable 19" profile shelves.
- Doors: ventilated, air passage 86%
- standard swivelling lever lock, universal key EK333, multi-point locking
- split rear door
- full front door
- Doors are compatible for the installation of a TANlock3 or TANlock1 swinghandle.
- 2 lockable side panels (split) with universal key.
- Protection class: IP00.
- Standard: Roof plate with 2 cable entries 1.000x88mm (brush strips), preparation for roof fan assembly (SR2VUxxxx).
- No bottom plate.
- Load capacity 2.000kg.
- Colour: RAL 7035 (alternatively also available in RAL 9005).
- Earthing and mounting set (1 PU=28pcs. cage nuts and M5 screws) included.

Technical Data

Net width (mm)	800,00
----------------	--------

Technical Data - continued

Net height (mm)	2.000,00
Netto depth (mm)	1.200,00
EAN	9004840996241
PRICE	100.100,00
Colour	RAL 7035 RAL 9005
Load capacity (static)	2.000Kg
Product type	Server rack

DESCRIPTION	Order No.
SCRAX 42HE-19"Enclosure,Vent. Doors, B=800xT=1.200xH=2.005mm	
By activating the "Request shopping cart" button, the customer advisor assigned to you will be informed and will contact you immediately.	SR1428215C