

Data Sheet for Article: SR3PDIEM02

PDU Essential Metered; 6xSchuko; 230V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/230V | 3,6kW
- Output: 6xCEE7/3 35° Socket
- Supply cable: 2.0m | 1.5mm²
- with CEE7/7 angled plug
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Technical Data

Net length (mm)	437,40
Net width (mm)	45,00

Technical Data - continued

Net height (mm)	60,00
Net weight (kg)	0,90
EAN	4057298233029
PRICE	1.265,00
Min. ambient temperature (°C)	-5
Max. ambient temperature (°C)	45
Rated voltage	230V
IP Rating	IP20
Product typ	Metered Essential
Number of sockets	6
Outlet type	6 x Schuko
Rated current (A)	16
Phases per feed	1
Connection type	CEE 7/7 (Type E/F)
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
mounting	Bracket (L-shape)

DESCRIPTION	Order No.
PDU Essential Metered; 6xSchuko; 230V; 16A Measurement per phase, incl. mounting bracket with screws	SR3PDIEM02