

Data Sheet for Article: SR3PDIPM03

PDU PRO Metered, 24xC13, 6xC19, 400V, 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 24x C13 IEC Socket + 6 x C19 IEC Socket
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)
- Packed in cardboard box
- Length 1409 mm

Technical Data

Net length (mm)	1.408,60
Net width (mm)	56,00
Net height (mm)	70,00
Net weight (kg)	4,28
EAN	4057298207877
PRICE	3.204,00
Min. ambient temperature (°C)	0
Max. ambient temperature (°C)	50
Rated voltage	400V
IP Rating	IP20
Product type	Metered
Number of sockets	30
Outlet type	24 x IEC320 C13 und 6 x IEC320 C19
Rated current (A)	16
Phases per feed	3
Connection type	CEE 16 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
mounting	Bracket (L-shape)

DESCRIPTION	Order No.
PDU PRO Metered, 24xC13, 6xC19, 400V, 16A	SR3PDIPM03
Measurement per phase, incl. mounting bracket with screws	