

Data Sheet for Article: SR3PDIPM09

# PDU PRO Metered, 36xC13, 6xC19, 400V, 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



## SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm<sup>2</sup>
- with CEE plug 32 A red
- Output: 36x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 2075 mm

## Technical Data

|                               |                                    |
|-------------------------------|------------------------------------|
| Net length (mm)               | 2.075,00                           |
| Net width (mm)                | 56,00                              |
| Net height (mm)               | 65,00                              |
| Net weight (kg)               | 6,77                               |
| EAN                           | 4057298207938                      |
| PRICE                         | 4.299,00                           |
| Min. ambient temperature (°C) | 0                                  |
| Max. ambient temperature (°C) | 50                                 |
| Rated voltage                 | 400V                               |
| IP Rating                     | IP20                               |
| Product typ                   | Metered                            |
| Number of sockets             | 42                                 |
| Outlet type                   | 36 x IEC320 C13 und 6 x IEC320 C19 |
| Rated current (A)             | 32                                 |
| Phases per feed               | 3                                  |
| Connection type               | CEE 32 A red                       |
| Protocol                      | LDAP                               |
|                               | IPv6                               |
|                               | IPv4                               |
|                               | DNS                                |
|                               | SNMPv1                             |
|                               | SSH                                |
|                               | HTTP                               |
|                               | SNMPv3                             |
|                               | SNMPv2                             |
|                               | NTP                                |
|                               | SSH2                               |
|                               | DHCP                               |
|                               | ModBus /TCP                        |
|                               | SMTP                               |
|                               | HTTPS                              |
|                               | SNMP Trap                          |
|                               | Syslog                             |
| mounting                      | Bracket (L-shape)                  |

| DESCRIPTION                                                                                                                                         | Order No.  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| PDU PRO Metered, 36xC13, 6xC19, 400V, 32A<br>Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller! | SR3PDIPM09 |