

Data Sheet for Article: SR3PDIPM10

# PDU PRO Metered, 30xC13, 6xC19, 400V, 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



## SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Zuleitung: 3,0 m | 4 mm<sup>2</sup>
- with CEE plug 32 A red
- Output: 30x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 1913 mm

## Technical Data

|                               |                                                                                                                                                        |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Net length (mm)               | 1.925,90                                                                                                                                               |
| Net width (mm)                | 56,00                                                                                                                                                  |
| Net height (mm)               | 65,00                                                                                                                                                  |
| EAN                           | 4057298207945                                                                                                                                          |
| PRICE                         | 4.240,00                                                                                                                                               |
| Min. ambient temperature (°C) | 0                                                                                                                                                      |
| Max. ambient temperature (°C) | 50                                                                                                                                                     |
| Rated voltage                 | 400V                                                                                                                                                   |
| IP Rating                     | IP20                                                                                                                                                   |
| Product typ                   | Metered                                                                                                                                                |
| Number of sockets             | 36                                                                                                                                                     |
| Outlet type                   | 30 x IEC320 C13 und 6 x IEC320 C19                                                                                                                     |
| Rated current (A)             | 32                                                                                                                                                     |
| Phases per feed               | 3                                                                                                                                                      |
| Connection type               | CEE 32 A red                                                                                                                                           |
| Protocol                      | LDAP<br>IPv6<br>IPv4<br>DNS<br>SNMPv1<br>SSH<br>HTTP<br>SNMPv3<br>SNMPv2<br>NTP<br>SSH2<br>DHCP<br>ModBus /TCP<br>SMTP<br>HTTPS<br>SNMP Trap<br>Syslog |
| mounting                      | Bracket (L-shape)                                                                                                                                      |

| DESCRIPTION                                                                                                                                         | Order No.  |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| PDU PRO Metered, 30xC13, 6xC19, 400V, 32A<br>Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller! | SR3PDIPM10 |