

Data Sheet for Article: SR3PDIP507

PDU PRO Switched, 36xCombo (C13,C15,C19,C21), 400V, 32A

Measurement per phase (measurement at socket level can be upgraded with license), switchable per socket, includes mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Switched
- Metering per phase
- Can be upgraded to measuring per socket at any time via licence (SR3PAB0011,SR3PAB0012,SR3PAB0013)
- switchable sockets
- Input: 32 A / 400 V | 22 kW
- Supply cable: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 36x Combo C13/C15/C19/C21
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)

- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </l

Technical Data

Net length (mm)	1.950,30
Net width (mm)	56,00
Net height (mm)	71,00
EAN	4057298230615
PRICE	7.412,00
Min. ambient temperature (°C)	0
Max. ambient temperature (°C)	50
Rated voltage	400V
IP Rating	IP20
Product type	Switched
Number of sockets	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Rated current (A)	32
Phases per feed	3
Connection type	CEE 32 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
mounting	Bracket (L-shape)

DESCRIPTION	Order No.
PDU PRO Switched, 36xCombo (C13,C15,C19,C21), 400V, 32A Measurement per phase (measurement at socket level can be upgraded with license), switchable per socket, includes mounting bracket with screws, not suitable for 42U enclosures or smaller!	SR3PDIPS07